


Twin wire-end ferrules with plastic collars



- Polypropylene conical entry funnel
- Heat-resistant up to 105 °C
- The entry funnel can also be manufactured from a non-flammable material on request

For conductors of 2 x 0.5-2 x 16 mm² (2 x AWG 20-2 x AWG6)

Material E-Cu, electro-galvanised

Dimensional tolerance acc. to DIN 46228 Part 4

Other colour code

Packed loose



Type	Ø mm ²	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H0.5/15	0.5	AWG 20	14.00	8	1.4		0.15	0.3	11	● Orange	500	9037200000
H0.5/16.5	0.5	AWG 20	16.00	10	1.4		0.15	0.3	13	● Orange	500	9037210000
H0.5/18.5	0.5	AWG 20	18.00	12	1.4		0.15	0.3	15	● Orange	500	9037220000
H0.75/15T	0.75	AWG 18	14.00	8	1.7		0.15	0.3	11	● LightBlue	500	9037610000
H0.75/17T	0.75	AWG 18	16.00	10	1.7		0.15	0.3	13	● LightBlue	500	9037620000
H0.75/19TS	0.75	AWG 18	19.00	12	1.7		0.15	0.3	21	● LightBlue	500	9202840000
H0.75/24.5T	0.75	AWG 18	24.00	18	1.7		0.15	0.3	21	● LightBlue	500	9037630000
H1.0/15D	1	AWG 17	15.00	8	2		0.15	0.3	11	● Red	500	9037440000
H1.0/20D	1	AWG 17	19.00	12	2		0.15	0.3	16	● Red	500	9037450000
H1.0/25.6D	1	AWG 17	25.00	18	2		0.15	0.3	22	● Red	500	9037460000
H1.5/16D	1.5	AWG 16	16.00	8	2.2		0.15	0.3	11	● Black	500	9037470000
H1.5/20D	1.5	AWG 16	20.00	12	2.2		0.15	0.3	15	● Black	500	9037480000
H1.5/25.6D	1.5	AWG 16	25.00	18	2.2		0.15	0.3	21	● Black	100	9037490000
H2.5/18.5T	2.5	AWG 14	19.00	10	2.8		0.15	0.4	13	● Grey	500	9037640000
H2.5/20.5T	2.5	AWG 14	21.00	12	2.8		0.15	0.4	15	● Grey	100	9037650000
H2.5/26.5T	2.5	AWG 14	27.00	18	2.8		0.15	0.4	21	● Grey	100	9037660000
H4.0/22T	4	AWG 12	22.00	12	3.5		0.2	0.5	15	● Orange	100	9037670000
H4.0/28T	4	AWG 12	28.00	18	3.5		0.2	0.5	21	● Orange	100	9037680000
H6.0/25T	6	AWG 10	23.00	12	4.5		0.2	0.5	20	● Green	100	9037690000
H6.0/29T	6	AWG 10	29.00	18	4.5		0.2	0.5	24	● Green	100	9037700000
H10.0/26T	10	AWG 7	24.00	12	5.8		0.2	0.5	17	● Brown	100	9037710000
H10.0/30T	10	AWG 7	30.00	18	5.8		0.2	0.5	23	● Brown	100	9037720000
H16.0/19T	16	AWG 6	29.00	16	8.3		0.3	0.6	20	○ White	50	9037730000
H16.0/38T	16	AWG 6	38.00	25	8.3		0.3	0.6	29	○ White	50	9037740000

Other colour code

In multi-pack bag



Type	Ø mm ²	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H0.75/17T	0.75	AWG 18	16.00	10	1.7		0.15	0.3	13	● LightBlue	500	9005140000
H1.0/15D	1	AWG 17	15.00	8	2.2		0.15	0.3	12	● Red	500	9018540000
H1.0/20D	1	AWG 17	19.00	12	2		0.15	0.3	16	● Red	500	9004760000
H1.5/16D	1.5	AWG 16	16.00	8	2.2		0.15	0.3	11	● Black	500	9004420000
H1.5/20D	1.5	AWG 16	20.00	12	2.2		0.15	0.3	15	● Black	500	9004750000
H2.5/18.5T	2.5	AWG 14	19.00	10	2.8		0.15	0.4	13	● Grey	250	9018580000
H2.5/20.5	2.5	AWG 14	21.00	12	2.8		0.15	0.4	15	● Grey	250	9005150000
H4.0/22T	4	AWG 12	2.00	12	3.5		0.2	0.5	15	● Orange	100	9018590000
H6.0/25T	6	AWG 10	23.00	12	4.5		0.2	0.5	20	● Green	100	9005160000
H10.0/26T	10	AWG 7	26.00	12	5.8		0.2	0.5	17	● Brown	100	9005170000