



- Polypropylene conical entry funnel
- Heat-resistant up to 105 °C
- The entry funnel can also be manufactured from a non-flammable material on request

For conductors from 1.5-16 mm<sup>2</sup> (AWG 26-250MCM)  
 Material E-Cu, electro-galvanised  
 Dimensional tolerance acc. to DIN 46228 Part 4

**Weidmüller colour code**

**Packed loose**



Type	Ø mm <sup>2</sup>	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H1.5/24 XS	1.5	AWG 16	24.00	14.5	1.8	6.8	0.15	0.3	13	● Black	100	9202870000
H2.5/24 XS	2.5	AWG 14	24.00	14.5	2.3	7.6	0.15	0.3	20	● Black	100	9202880000

**Weidmüller colour code**

**In multi-pack bag**



Type	Ø mm <sup>2</sup>	AWG	L1	L2	D1	D2	S1	S2	Stripping length	Colour	Qty.	Order No.
H1.5/17.5X	1.5	AWG 16	17.50	8	1.8	6.8	0.15	0.3	13	● Black	100	9006590000
H1.5/19.5X	1.5	AWG 16	19.50	10	1.8	6.8	0.15	0.3	15	● Black	100	9006630000
H2.5/17.5X	2.5	AWG 14	17.50	8	2.3	7.6	0.15	0.3	14	● Blue	100	9006670000
H2.5/21.5X	2.5	AWG 14	21.50	12	2.3	7.6	0.15	0.3	17	● Blue	100	9006710000
H4.0/19.5X	4	AWG 12	19.50	10	2.9	7.8	0.2	0.3	14	● Grey	100	9006750000
H6.0/23.0X	6	AWG 10	23.00	12	3.6	8.1	0.2	0.3	17	● Yellow	100	9006790000
H10.0/24.5X	10	AWG 7	24.00	12	4.6	9.6	0.2	0.3	17	● Red	100	9006830000
H16.0/25.5X	16	AWG 6	25.50	12	6	11.9	0.2	0.3	26	● Blue	100	9006870000