

Crimping tools for other contacts

- Ratchet for precise crimping
- Release option in the event of incorrect operation
- With end stop for exact positioning of the contacts

CTI 6 G

0,5...6 mm²

For PVC, PC- and polyamide-insulated connectors

- ~AWG 21...10
- Parallel crimp profile for crimping contact and insulation in one step



CTI 6

0,5...6 mm²

For PVC, PC- and polyamide-insulated connectors

- ~AWG 21...10
- Double-crimp profile for crimping contact and insulation in one step



Technical data

Description of contact	
Type of contact	
Crimping range	mm ²
Crimping range 1 (with multiple crimping positions)	mm ²
Crimping range 2 (with multiple crimping positions)	mm ²
Crimping range 3 (with multiple crimping positions)	mm ²
Plug width	mm
Tool data	
Length	mm
Weight	g
Note	

Ordering data

Version
Note

CTI 6 G		
Insulated connector		
Crimping range	0.5...6	
Crimping range 1 (with multiple crimping positions)	0.5...1.5	
Crimping range 2 (with multiple crimping positions)	1.1...2.5	
Crimping range 3 (with multiple crimping positions)	2.6...6	
Plug width		
Tool data		
Length	250	
Weight	747	
Note		

Type	Qty.	Order No.
CTI 6 G	1	9202850000
CTI 6 G ZERT	1	1292880000
Additional accessories can be found in Chapter J		

CTI 6		
Insulated connector		
Crimping range	0.5...6	
Crimping range 1 (with multiple crimping positions)	0.5...1.5	
Crimping range 2 (with multiple crimping positions)	1.1...2.5	
Crimping range 3 (with multiple crimping positions)	2.6...6	
Plug width		
Tool data		
Length	250	
Weight	730	
Note		

Type	Qty.	Order No.
CTI 6	1	9006120000
CTI 6 ZERT	1	9017290000
Additional accessories can be found in Chapter J		