

2-pole voltage tester

2-pole voltage tester

- Automatic testing, identification and display of voltage type (AC or DC) and polarity
- Concisely arranged LED display
- Phase testing relative to earth
- Polarity testing
- Continuity and semiconductor testing
- Touch protection because of high input resistance
- Large voltage range
- IP 65

Combi-Check Pro

2-pole voltage tester



- Phase sequence indicator
- Single-pole phase testing
- Selectable load for residual current test
- Batteries included

Combi-Check

2-pole voltage tester



- Phase sequence indicator
- Single-pole phase testing
- Batteries included



Technical data

Nominal voltage
Input resistance, voltage
Peak voltage resistance
Frequency range, min.
Measuring range category
Display
Operating temperature, min.
Protection degree
Approvals
Weight
Note

COMBI CHECK PRO
6 V...690 V AC/DC
On operating the double switch $\geq 300 \text{ k}\Omega$
8 kV
0...100 Hz
CAT IV - 600V/ CAT III - 690V
LED
-15...45 °C
IP 65
EN/IEC 61243-3 :2010-10 (VDE 0682 Part 401)
290 g
Note

COMBI CHECK
6 V...690 V AC/DC
8 kV
0...100 Hz
CAT IV - 600V/ CAT III - 690V
LED
-15...45 °C
IP 65
290 g
Note

Ordering data

Version
Note

Type	Qty.	Order No.
COMBI CHECK PRO	1	1279330000
COMBI CHECK PRO 2MM	1	1279550000
Note		

Type	Qty.	Order No.
COMBI CHECK	1	9918860000
Combi Check 2MM	1	9204230000
Note		

Accessories

Note

Type	Qty.	Order No.
SKAI POUCH	1	9201520000
BATTERY 1.5 V (AAA)	2	9201310000
BAT-DE	1	1332410000
PRSPSU	1	1332420000
Note		

Type	Qty.	Order No.
SKAI POUCH	1	9201520000
BATTERY 1.5 V (AAA)	2	9201310000
BAT-DE	1	1332410000
PRSPSU	1	1332420000
Note		