

MARTINDALE
ELECTRIC

Specification MM65 Digital Multimeter



ELECTRICAL

All specified accuracies are at 23°C ± 5°C, <75% RH for 1 year

Temperature coefficient: 0.1 x (specified accuracy) per °C (0°C to 18°C, 28°C to 50°C)

DC VOLTAGE

Ranges: 340mV, 3.4V, 34V, 340 V, 600V

Resolution: 0.1mV, 0.001V, 0.01V, 0.1V, 1V

Accuracy: ± (1.0 % of rdg + 2 dgts)

Input impedance: 340mV: >100 MΩ;
3.4V: 10 MΩ; 34V to 600V: 9.1MΩ.

Overload protection: 600V DC or AC rms

AC VOLTAGE (50Hz to 500Hz)

Ranges: 3.4V, 34V, 340V, 600V

Resolution: 0.001V, 0.01V, 0.1V, 1V

Accuracy: ± (2.0 % of rdg + 5 dgts)

Input impedance: 3.4V: 10MΩ; 34V to 600V: 9.1MΩ

Overload protection: 600V DC or AC rms

DC CURRENT

Ranges: 340μA, 3400μA, 34mA, 340mA, 10A *

Resolution: 0.1μA, 1μA, 0.01mA, 0.1mA, 0.01A

Accuracy: 340μA to 340mA ranges ± (2.0 % of rdg + 2 dgts)

10A range ± (3.0 % of rdg + 3 dgts)

*Current on 10A range applied for 60 seconds max followed by a 10 minute cooling period

Input protection: 0.5A/500V fast blow ceramic fuse

10A/500V fast blow ceramic fuse

MARTINDALE
ELECTRIC

Specification MM65 Digital Multimeter

AC CURRENT (50Hz to 500Hz)

Ranges: 340μA, 3400μA, 34mA, 340mA, 10A *

Resolution: 0.1μA, 1μA, 0.01mA, 0.1mA, 0.01A

Accuracy: 340μA to 340mA ranges ± (2.5% of rdg + 5 dgts)

10A range ± (3.5 % of rdg + 5 dgts) *

* Current on 10A range applied for 60 seconds max followed by a 10 minute cooling period

Input protection: 0.5A/500V fast blow ceramic fuse 10A/500V fast blow ceramic fuse

RESISTANCE

Ranges: 340Ω, 3.4kΩ, 34kΩ, 340kΩ, 3.4MΩ, 34MΩ

Resolution: 0.1Ω, 0.001kΩ, 0.01kΩ, 0.1kΩ, 0.001MΩ, 0.01MΩ

Accuracy: 340Ω to 340kΩ ranges ± (1.5% of rdg + 4 dgts)

3.4MΩ range ± (2.5% of rdg + 4 dgts)

34MΩ range ± (5.0% of rdg + 5 dgts)

Open circuit voltage: -0.45V DC (-1.2V DC on 340 range)

Overload protection: 500V DC or AC rms

CONTINUITY

Audible indication: < 35Ω

Response time: 500ms

Overload protection: 500V DC or AC rms

DIODE TEST

Test current: 1.0mA approx

Resolution: 10mV

Accuracy: ± (3.0% rdg + 3 dgts)

Audible indication: <0.25 V

Open circuit voltage: 3.0V DC typical

Overload protection: 500V DC or AC rms

MARTINDALE
ELECTRIC

Specification MM65 Digital Multimeter

GENERAL


Display: 3½ digit liquid crystal display with a maximum reading of 3400

Analog bargraph: 34 segments with measurement 12 times per second

Polarity: Automatic, positive implied, negative polarity indication

Overrange: (OL) or (-OL) is displayed

Zero: Automatic.

Low battery indication:  symbol is displayed when the battery voltage drops below the operating level

Measurement rate: 2 times per second, nominal

Auto power off: After approx 10 minutes

Operating environment: 0°C to 50°C at < 70% RH

Storage temperature: -20°C to 60°C at < 80% RH

Altitude: Up to 2000m

Power: Single standard 9 volt battery, NEDA 1604, JIS006P, IEC 6F22

Battery Life: 200 hours typical with carbon-zinc

Dimensions: 165mm (H) x 78mm (W) x 42.5mm (D)

Weight: Approx. 285g

Includes: TL16 test leads, Magnetic strap, 1 x spare fuse, 9V battery (installed) and instructions.

SAFETY:

Conforms to BS EN 61010-1, CAT III 600 V.

Class II Double Insulation.

Pollution Degree: 2 for indoor use.

TL16 test leads conform to BS EN 61010-031 CAT III 1000V, CAT IV 600V, 10A.

EMC: Conforms to BS EN 61326.

Check out what else you can get from Martindale:

- 17th Edition Testers
- Accessories
- Calibration Equipment
- Continuity Testers
- Electricians' Kits
- Environmental Products
- Full Calibration & Repair Service
- Fuse Finders
- Digital Clamp Meters
- Digital Multimeters
- Labels
- Microwave Leakage Detectors
- Motor Maintenance Equipment
- Multifunction Testers
- Non-trip Loop Testers
- Pat Testers & Accessories
- Phase Rotation Testers
- Proving Units
- Socket Testers
- Thermometers & Probes
- Test Leads
- Voltage Indicators
- Specialist Metrohm Testers (4 & 5kV)
- Specialist Drummond Testers

MARTINDALE
ELECTRIC

Martindale Electric Company Limited
Metrohm House, Penfold Trading Estate, Imperial Way, Watford WD24 4YY, UK
Tel: +44(0)1923 441717 Fax: +44 (0)1923 446900
E-mail: sales@martindale-electric.co.uk
Website: www.martindale-electric.co.uk



© 2012 Martindale Electric Company Ltd.
Registered in England No. 3387451. E. & O.E. Document Rev1 LITMM65